


JTextComponent 4

・エディターキットの利用



```
import java.awt.BorderLayout;
import java.awt.Color;
import java.awt.Dimension;

import javax.swing.Action;
import javax.swing.JFrame;
import javax.swing.JMenu;
import javax.swing.JMenuBar;
import javax.swing.JPanel;
import javax.swing.JScrollPane;
import javax.swing.JTextPane;
import javax.swing.SwingUtilities;
import javax.swing.text.StyledEditorKit;

/**
 * @see http://java.sun.com/docs/books/tutorial/uiswing/components/generaltext.html
 */
public class JTextTest4 {
    private JFrame frame;
    private JTextPane txtPane;

    /**
     * StyledEditorKit を利用する
     */
    private JMenu getMenu() {
        JMenu menu = new JMenu("Style");
        Action action = null;

        action = new StyledEditorKit.BoldAction();
        action.putValue(Action.NAME, "Bold");
        menu.add(action);
```

```

action = new StyledEditorKit.ItalicAction();
action.putValue(Action.NAME, "Italic");
menu.add(action);

action = new StyledEditorKit.UnderlineAction();
action.putValue(Action.NAME, "Underline");
menu.add(action);

menu.addSeparator();

menu.add(new StyledEditorKit.FontSizeAction("12", 12));
menu.add(new StyledEditorKit.FontSizeAction("14", 14));
menu.add(new StyledEditorKit.FontSizeAction("18", 18));

menu.addSeparator();

menu.add(new StyledEditorKit.FontFamilyAction("Serif", "Serif"));
menu.add(new StyledEditorKit.FontFamilyAction("SansSerif", "SansSerif"));

menu.addSeparator();

menu.add(new StyledEditorKit.ForegroundAction("Red", Color.red));
menu.add(new StyledEditorKit.ForegroundAction("Green", Color.green));
menu.add(new StyledEditorKit.ForegroundAction("Blue", Color.blue));
menu.add(new StyledEditorKit.ForegroundAction("Black", Color.black));

return menu;
}
private void createUI() {
    frame = new JFrame("TextTest3");
    frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);

    txtPane = new JTextPane();
    txtPane.setPreferredSize(new Dimension(200,100));

    JPanel basePanel = new JPanel(new BorderLayout());
    basePanel.add(new JScrollPane(txtPane), BorderLayout.CENTER);

    // メニューを作成
    JMenu menu = getMenu();
    JMenuBar mb = new JMenuBar();
    mb.add(menu);
    frame.setJMenuBar(mb);

    frame.getContentPane().add(basePanel);
    frame.pack();
    frame.setVisible(true);
}
public static void main(String[] args) {
    SwingUtilities.invokeLater(
        new Runnable(){
            public void run() {
                JTextTest4 jft = new JTextTest4();
                jft.createUI();
            }
        }
    );
}
}

```